

CHARACTERISTICS

Sunshade system for protecting small and large openings from the sun's rays and bad weather, thanks to its concept that combines safety, flexibility, and a pleasant appearance. The extruded aluminium elements in three different sizes contain sound insulating material.



INSULATED
SLATS



MINIMUM
FOOTPRINT

SKURO SIKURO


SUNSHADE SYSTEM

SKURO SIKURO


WIDTH OF SLATS	125 x 13 mm 151 x 13 mm 177 x 13 mm
THICKNESS OF SLATS	13 mm
THICKNESS OF TRACKS	40 mm
HEIGHT OF BOTTOM TRACK	20 mm
WEIGHT	10-12 kg/m²
MAXIMUM WIDTH	4000 mm
MAXIMUM HEIGHT	2800 mm
PACKING	RIGHT / LEFT
PACK DIMENSIONS	125 SLATS - 11% 151 SLATS - 9% 177 SLATS - 8%
PACKING OF SLATS	EXTERNAL
SLIDING	TOP
WIND RESISTANCE CERTIFICATION - EN 13659	CLASS 6

OPENING SET UP


PACKING TO THE LEFT



PACKING TO THE RIGHT



PACK DIVIDED ON TWO SIDES



For finishes, visit the website sunroom.it

The view is always considered to be from the inside.