

CHARACTERISTICS

Always made to measure, the S.60 TT folding door has no length limits and offers great freedom of design. Also, the ability to insert a low threshold minimizes the thickness in transit to greater facilitate the connection between the indoors and outdoors.



THERMAL
BREAK



LOW
THRESHOLD
BOTTOM TRACK



ENERGY
SAVINGS

S.60 TT

FOLDING DOOR

S.60 TT


THERMAL BREAK SYSTEM

TOP TRACK PROFILE	70 mm
MAXIMUM PANEL WIDTH	1000 mm
MAXIMUM PANEL HEIGHT	3000 mm
MAXIMUM PANEL WEIGHT	60 kg
WEIGHT OF GLAZED UNIT	8-11 kg/m² excluding glazing
THERMAL INSULATED PROFILES	✓
ADJUSTMENTS	✓
SLIDING	BOTTOM TOP
HEIGHT OF BOTTOM TRACK (WITH BOTTOM SLIDING)	STANDARD - 70 mm UPON REQUEST - LOWERED 18 mm
HEIGHT OF BOTTOM TRACK (WITH TOP SLIDING)	STANDARD - 50 mm
COLOUR OF ACCESSORIES	BLACK GREY
CLOSURES	TOP, BOTTOM AND FRAME
OPENING FROM OUTSIDE WITH A KEY	UPON REQUEST
HINGED PANEL LOCK	1 POINT / MULTIPOINT (UPON REQUEST)
INWARD / OUTWARD OPENING	✓
RIGHT / LEFT PACKING	✓
SLIDING CORNER TYPE	UPON REQUEST
GATHERED GLAZED UNIT DIMENSIONS	10%
GLAZING	27/32 mm 38/43 mm
WATER TIGHTNESS CERTIFICATION EN 1027 - EN 12208	CLASS 5A
AIR PERMEABILITY CERTIFICATION EN 1026 - EN 12207	CLASS 4
WIND RESISTANCE CERTIFICATION EN 12211 - EN 12210	CLASS B3
THERMAL TRANSMITTANCE 4 PANEL GLAZED UNIT - 3400 x 2500 mm GLASS Ug = 0.6 W/m²k, PSI = 0.05 W/mk	Uw = 1.30 W/m²k




For finishes, visit the website sunroom.it


OPENING MODULE SET UP




1




2




3




4




5




6




7




8




9




10




11




12




13




14




15




16



17



18



19

————— INWARD OPENING

----- OUTWARD OPENING

For good operation of the glazed unit, always follow the type indicated.