

## CHARACTERISTICS

Sunshade system for protecting small and large openings from the sun's rays and bad weather, thanks to its concept that combines safety, flexibility, and a pleasant appearance. The extruded aluminium elements in three different sizes contain sound insulating material.



INSULATED  
SLATS



MINIMUM  
FOOTPRINT

# SKURO SIKURO


SUNSHADE SYSTEM

# SKURO SIKURO


WIDTH OF SLATS	125x13 mm 151x13 mm 177x13 mm
THICKNESS OF SLATS	13 mm
THICKNESS OF TRACKS	40 mm
HEIGHT OF BOTTOM TRACK	20 mm
WEIGHT	10-12 Kg/m <sup>2</sup>
MAXIMUM WIDTH	4000 mm
MAXIMUM HEIGHT	2800 mm
PACKING	RIGHT / LEFT
PACK DIMENSIONS	SLATS 125 - 11% SLATS 151 - 9% SLATS 177 - 8%
PACKING OF SLATS	EXTERNAL
SLIDING	TOP
WIND RESISTANCE CERTIFICATION - EN 13659	CLASS 6

# OPENING SET UP


## PACKING TO THE LEFT



## PACKING TO THE RIGHT



## PACK DIVIDED ON TWO SIDES



For finishes, visit the website [sunroom.it](http://sunroom.it)

The view is always considered to be from the inside.