

CHARACTERISTICS

Parallel sliding door system with a strong aesthetic impact that is also resistant and practical. The panels, without vertical profiles, are always made to measure in tempered glass, while the stainless steel accessories ensure safety and stability.



PATENTED
DESIGN



STAINLESS
STEEL

TUTTOVETRO SLIDE

FRAMELESS SYSTEMS

TUTTOVETRO SLIDE

ALUMINIUM SYSTEM

NUMBER OF TRACKS	2/3/4/5/6
PANEL OVERLAP	13 mm
MAXIMUM PANEL WIDTH	1300 mm
MAXIMUM PANEL HEIGHT	3000 mm
MAXIMUM PANEL WEIGHT	100 kg
WEIGHT OF GLAZED UNIT	30+5 kg/m ² including glazing 12 mm 25+5 kg/m ² including glazing 10 mm
PANEL ADJUSTMENTS	✓
GASKETS	UPON REQUEST
SLIDING	BOTTOM
SLIDING ACCESSORIES	STAINLESS STEEL
HEIGHT OF BOTTOM TRACK	21 mm
RECESSED TRACK	UPON REQUEST
COLOUR OF ACCESSORIES	SILVER
CLOSURES	SIDE ON FRAME / FLOOR (UPON REQUEST)
OPENING FROM OUTSIDE WITH A KEY	UPON REQUEST
RIGHT / LEFT SLIDING	✓
SLIDING CORNER TYPE	UPON REQUEST
GLAZING	10 mm 12 MM
WATER TIGHTNESS CERTIFICATION EN 1027 - EN 12208	CLASS 1A
AIR PERMEABILITY CERTIFICATION EN 1026 - EN 12207	CLASS 1

OPENING MODULE SET UP

2 PANELS 2 TRACKS - LEFT INTERNAL PANEL




2 PANELS 2 TRACKS - RIGHT INTERNAL PANEL




4 PANELS 2 TRACKS - CENTRAL INTERLOCK




3 PANELS 3 TRACKS - LEFT INTERNAL PANEL




3 PANELS 3 TRACKS - RIGHT INTERNAL PANEL




6 PANELS 3 TRACKS - CENTRAL INTERLOCK




4 PANELS 4 TRACKS - LEFT INTERNAL PANEL




4 PANELS 4 TRACKS - RIGHT INTERNAL PANEL




8 PANELS 4 TRACKS - CENTRAL INTERLOCK




5 PANELS 5 TRACKS - LEFT INTERNAL PANEL




5 PANELS 5 TRACKS - RIGHT INTERNAL PANEL




10 PANELS 5 TRACKS - CENTRAL INTERLOCK



6 PANELS 6 TRACKS - LEFT INTERNAL PANEL



6 PANELS 6 TRACKS - RIGHT INTERNAL PANEL



12 PANELS 6 TRACKS - CENTRAL INTERLOCK



For finishes, visit the website sunroom.it

The view is considered to be from the inside. For good operation of the glazed unit, always follow the type indicated.