

CHARACTERISTICS

Folding door with modular elements in non-thermal aluminium profiles that has excellent sliding motion as well as the unique possibility of creating curving closures.

Its panels are always custom designed, while the simple forms and guarantee of long-lasting use make it an excellent choice.



MINIMUM
FOOTPRINT



CURVING
CLOSURES

S.30



















FOLDING DOOR

S.30

ALUMINIUM SYSTEM

TOP TRACK PROFILE	40 mm
MAXIMUM PANEL WIDTH	800 mm
MAXIMUM PANEL HEIGHT	3000 mm
MAXIMUM PANEL WEIGHT	35 kg
WEIGHT OF GLAZED UNIT	6-10 kg/m ² EXCLUDING GLAZING
ADJUSTMENTS	✓
SLIDING	TOP BOTTOM
HEIGHT OF BOTTOM TRACK (WITH BOTTOM SLIDING)	STANDARD - 62 mm
	STANDARD - 55 mm
HEIGHT OF BOTTOM TRACK (WITH TOP SLIDING)	UPON REQUEST - LOWERED 25 mm - RECESSED 10 mm (RECESS 25 mm)
COLOUR OF ACCESSORIES	BLACK
CLOSURES	TOP, BOTTOM AND FRAME
OPENING FROM OUTSIDE WITH A KEY	UPON REQUEST
HINGED PANEL LOCK	1 POINT / MULTIPOINT (UPON REQUEST)
INWARD / OUTWARD OPENING	✓
RIGHT / LEFT PACKING	✓
SLIDING CORNER TYPE	UPON REQUEST
CURVED OR SEGMENT OPTION	UPON REQUEST
GATHERED GLAZED UNIT DIMENSIONS	8%
GLAZING	6/20 mm
WATER TIGHTNESS CERTIFICATION EN 1027 - EN 12208	CLASS 5A
AIR PERMEABILITY CERTIFICATION EN 1026 - EN 12207	CLASS 3
WIND RESISTANCE CERTIFICATION EN 12211 - EN 12210	CLASS B1

OPENING MODULE SET UP



———— INWARD OPENING
 - - - - - OUTWARD OPENING



For finishes, visit the website sunroom.it

For good operation of the glazed unit, always follow the type indicated.