

CHARACTERISTICS

Safe and robust sliding door that guarantees a significant aesthetic impact for any environment. Particularly solid, it can also be used to create large panels and glazing of various thicknesses. There are various types of handles available, including an ergonomic one. You can choose between the thermal break or non-thermal versions.



THERMAL
BREAK



ERGONOMIC
HANDLE



ENERGY
SAVINGS

S.70 | S.70 TT

SLIDING DOOR

TECHNICAL DATA SHEET

S.70 | S.70 TT

| | ALUMINIUM SYSTEM | THERMAL BREAK SYSTEM |
|--|---|---|
| NUMBER OF TRACKS | 2/3 | 2/3 |
| DIMENSIONS OF CENTRAL NODE | STANDARD - 87 mm REDUCED - 40 mm | STANDARD - 87 mm REDUCED - 40 mm |
| MAXIMUM PANEL WIDTH | 2400 mm | 2400 mm |
| MAXIMUM PANEL HEIGHT | 3000 mm | 3000 mm |
| MAXIMUM PANEL WEIGHT | 130 Kg | 130 kg |
| WEIGHT OF GLAZED UNIT | 8-15 kg/m ² EXCLUDING GLAZING | 8-15 kg/m ² EXCLUDING GLAZING |
| THERMAL INSULATED PROFILES | NO | ✓ |
| PANEL ADJUSTMENTS | ✓ | ✓ |
| SLIDING | BOTTOM | BOTTOM |
| HEIGHT OF BOTTOM TRACK | 53 mm | 53 mm |
| RECESSED TRACK | UPON REQUEST | UPON REQUEST |
| COLOUR OF ACCESSORIES | BLACK GREY | BLACK GREY |
| CLOSURES | SIDE ON FRAME | SIDE ON FRAME |
| OPENING FROM OUTSIDE WITH A KEY | UPON REQUEST | UPON REQUEST |
| RIGHT / LEFT SLIDING | ✓ | ✓ |
| SLIDING CORNER TYPE | UPON REQUEST | UPON REQUEST |
| GLAZING | 4/11 mm 20/27 mm | 20 mm 27 mm |
| WATER TIGHTNESS CERTIFICATION EN 1027 - EN 12208 | CLASS 7A | CLASS 7A |
| AIR PERMEABILITY CERTIFICATION EN 1026 - EN 12207 | CLASS 3 | CLASS 3 |
| WIND RESISTANCE CERTIFICATION EN 12211 - EN 12210 | CLASS B3 | CLASS B3 |
| THERMAL TRANSMITTANCE 2 PANEL GLAZED UNIT - 4000 x 2500 mm GLASS Ug = 1.00 W/m ² k, Psi = 0.05 W/mk | - | UW = 1.65 W/m ² k |




For finishes, visit the website sunroom.it

OPENING MODULE SET UP

2 PANELS 2 TRACKS - LEFT INTERNAL PANEL




2 PANELS 2 TRACKS - RIGHT INTERNAL PANEL




4 SCHIEBEFLÜGEL 2 SPUREN ZENTRALER VERSCHLUSS



3 PANELS 3 TRACKS - LEFT INTERNAL PANEL



3 PANELS 3 TRACKS - RIGHT INTERNAL PANEL



6 PANELS 3 TRACKS - CENTRAL INTERLOCK



The view is considered to be from the inside. For good operation of the glazed unit, always follow the type indicated.